

10MS - 10" Submersible motors water cooled rewindable - PVC insulated

Type	Rated power		Efficiency 4/4	Power Factor 4/4	Rated current A	RPM	starts max (per hour)	Starting			
	kW	HP						Direct		Star/Delta	Statoric
			%	cosφ	400V	Ma/Mn		Ia/In	Ia/In	Ia/In	
10MS 5900	59	80	85	0,83	116	2910	8	1,88	4,80	1,6	3,3
10MS 7500	75	100	86	0,84	145	2910		1,83	4,95	1,7	3,4
10MS 9200	92	125	87	0,87	176	2900		1,76	5,27	1,7	3,7
10MS 11000	110	150	87	0,86	210	2870	6	1,88	5,45	1,8	3,8
10MS 13200	132	180	87,5	0,87	255	2910		1,78	5,50	1,8	3,8
10MS 15000	150	200	88	0,85	290	2920		1,88	5,50	1,9	3,8
10MS 17000	170	230	88	0,85	330	2910		1,89	5,55	1,9	3,9
10MS 19000	190	260	88	0,84	375	2910		1,87	5,53	1,9	3,9

Type	L	cable length	cable section		Max water °C		Axial Thrust	Weight
			direct	star/delta	PVC	PE2+PA		
	mm	mt	400V	400/690V			N	Kg.
10MS 5900	1420	3,5	(1x25)x3	(1x25)x6	25°C	45°C	60.000	267
10MS 7500	1540							305
10MS 9200	1670	4,5	(1x50)x3	(1x35)x6	-	-	-	348
10MS 11000	1810							394
10MS 13200	1910							421
10MS 15000	2030		(1x70)x3	(1x50)x6	-	-	-	450
10MS 17000	2130							490
10MS 19000	2230	(1x95)x3	(1x50)x6	-	-	-	530	

